

Tape Adaptors & Accessories

FITTINGS

D-Barb, PE & PVC Pipe, Lay-Flat & Tape Connections



13 mm D-Barb x Ø16 Tape Connector
Flex Connect™ with Lay-Flat Adaptor x Ø16 Tape Connector



Take-Off with Gasket x Ø16 Tape Connector, For PE Pipe
Ø16 Tape Connector

Adaptors Connection Type		PACKAGING								Material	
		Packs				Dimensions of Assembled Adaptors					
		Order Code	Quantity per Bag	Bags per Carton	Weight per Carton (kg)	Height	Width	Length	Weight		
						mm				g	Body
	13 mm D-Barb Ø16 Tape Connector	207025	50	16	8.0	26	27	72.7	8.6	U.V. Stabilized	
	13 mm D-Barb Ø22 Tape Connector	207085	50	10	9.3	45	33	76	16.4		
	17 mm D-Barb Ø22 Tape Connector	207095	50	10	9.5	45	33	76	16.8		
	Take-Off, For 15 mm Hole Gasket Ø16 Tape Connector (Includes Gasket)	207035	50	12	7.1	37	27	59.2	8.2		
	Take-Off, For 16 mm Hole Gasket Ø16 Tape Connector (Includes Gasket)	207045	50	12	7.4	37	27	64.1	8.6		
	Take-Off with Gasket Ø16 Tape Connector, For PE Pipe	207055	50	16	9.2	37	27	63.2	10.1		
	Take-Off with Gasket Ø22 Tape Connector, For PE Pipe	207105	50	12	15.0	45	33	65.2	23.5		
	Ø16 Tape Connector	207075	50	10	7.6	27	27	81.0	13.1		
	Ø22 Tape Connector	207115	50	7	10.0	33	33	85	25.7		
	Flex Connect™ with Lay-Flat Adaptor Ø16 Tape Connector	207065	50	10	12.7	53	35	65.2	23.4		
	Flex Connect™ with Lay-Flat Adaptor Ø22 Tape Connector	207125	50	7	10.5	53	35	65.2	23.4		
	Flex Connect™ without Lay-Flat Adaptor Ø16 Tape Connector	202925	50	10	8.1	36	29	65.2	14.2		
	Flex Connect™ without Lay-Flat Adaptor Ø22 Tape Connector	203045	50	8	8.2	45	33	65.2	18.1		
	End Plug Ø16 Tape Connector	210695	50	16	8.4	36	27	68.7	9.1		
	End Plug Ø22 Tape Connector	210705	50	10	8.9	45	33	70.5	15.7		
	1/2" NPT/M Ø16 Tape Connector	210715	50	16	9.3	36	27	65.2	10.2		
	1/2" NPT/M Ø22 Tape Connector	210725	50	10	9.4	45	33	67	16.7		
	3/4" BSP/M Ø16 Tape Connector	212725	50	15	8.4	36	27	66	9.7		
	3/4" BSP/M Ø22 Tape Connector	212745	50	10	8.5	45	33	68	14.8		
	250 Series Barb Ø16 Tape Connector	212505	50	18	7.5	36	27	64	7.9		

FEATURES and BENEFITS

- The Lay-Flat Hexagon installation tool with a wrench attachment in the head of the handle for screwing and tightening of the Lay-Flat Lock Nut.
- The Lock Nut secures the eye connection to the Lay-Flat Hose and creates a leak free connection.
- The eye connection fitting has a Sealing Cap available to minimize soil intrusion when storing.

Accessories for Lay-Flat Hose, Valves, Adaptors & Sprinkler Assemblies



Installation Key For Lay-Flat Branches



Lay-Flat Adaptor, Eye Connection with Lay-Flat Lock Nut



Lay-Flat Flex Connect™ Sealing Cap



Lay-Flat Hose Punch



Counter Weight

Accessories		PACKAGING								Material
		Packs				Dimensions of Accessories				
		Order Code	Quantity per Bag	Bags per Carton	Weight per Carton (kg)	Height	Width	Length	Weight	
						mm			g	
	400 Series Barb Ø16 Tape Connector	211125	50	16	8.3	36	27	65.2	8.9	U.V. Stabilized
	400 Series Barb Ø22 Tape Connector	211135	50	10	9.1	45	33	67	16.0	
	13 mm D-Barb x Take-Off for 16 mm Hole Gasket (Includes Gasket)	207145	50	20	6.5	20	20	53	5.2	
	Top Hat Gasket Hole 15	105445	50	80	9.7	20	20	17	1.8	
	Top Hat Gasket Hole 16	105055	50	80	9.7	23	23	18	1.9	
	Double Flange Gasket Hole 16	105425	50	80	10.1	24	24	12.7	2.0	
	Lay-Flat Adaptor, Eye Connection with Lay-Flat Lock Nut	205515	50	50	20.6	28	28	23	8.5	
	Lay-Flat Flex Connect™ Sealing Cap	107785	50	75	17.9	28	28	8	2.8	
	Installation Key for Lay-Flat Branches	105432	10	30	14.9	62	20	142	45.0	
	Lay-Flat Hose Punch (Hole Size Ø14 mm)	207138	1	40	8.5	155	37	160	190.4	

Accessories & Adaptors		PACKAGING											Material	
		Order Code		Quantity per Bag		Bags per Carton		Weight per Carton (kg)		Dimensions of Accessories				
		Packs	Bulk	Packs	Bulk	Packs	Bulk	Packs	Bulk	Length	Width	Depth		Weight
										mm			g	
	Counter Weight	106624	010662	25	250	10	1	10.7	10.6	95	29	29	38.5	U.V. Stabilized
	Adaptor, 4.5 mm Barb x 4.5 mm Barb / 10-32 UNF Thread	106616	010661	100	1000	200	22	16.9	15.2	32.5	16	16	5.7	
Micro Tube Flexible PVC		Colour	Order Codes	Coils per Carton		Coil Dimensions								
		Bulk	Bulk	Bulk		Dia.	Height	Weight						
						mm		kg						
	20 meters	White	010737	15		175	80	0.70						
	20 meters	Black	010056											
	30 meters	Black	010057	10		200	90	1.02						
	300 meters	Black	010131			355	225	10.5						